

<b>AXON VB MANURE SPREADERS</b>	<b>(Twin Vertical Beaters)</b>				
	<b>Model</b>	<b>800</b>	<b>900</b>	<b>1000</b>	<b>1400</b>
<b>STANDARD SPECIFICATION</b>					
Volume - Level m3	8.6	9.5	10	14	16
Volume - Heaped m3	12	15	16	22-23	26
Axle - 10 Stud mm	110x110	110x110	110x110	150x150	150x150
Standard Wheels	520/85 R38	520/85 R38	580/70 R38	580/70 R38	710/70 R38
Standard PTO Input rpm	1000	1000	1000	1000	1000
Rear Drive Shaft mm	50	50	60	60	60
Standard Floor Chains mm	2 x 20	2 x 20	2 x 20	2 x 20	2 x 20
Floor Drive Gearbox (SISP/Berma)	SISP 500	SISP 500	RT800	RT800	RT800
<b>DIMENSIONS mm</b>					
Overall Length	7040	7040	7040	7790	8590
Overall Height	3036	3036	3300	3300	3300
Overall Width	2850	2850	2850	2950	3100
Internal Length	4400	4400	4730	5480	6230
Internal Height	1050	1350	1400	1400	1400
Internal Width - at narrowest point	1500	1500	1500	1500	1500
Internal Width - at widest point	2200	2200	2200	2200	2200
Loading Height	2315	2620	2590	2890	2590

The manufacturer reserves the right to alter specifications without notice.